

# VOLGELAATSMASKER

## DRÄGER X-PLORE® 6300

Tuinbouwtechniek  
& -benodigdheden



The Dräger X-plore® 6300 is designed for use by professionals in industry, and meets the highest demands for reliability, fit and comfort. Together with the respiratory filters from Dräger's comprehensive X-plore® Rd40 filter range, it has proven suitable for a wide range of different applications. For longer application periods this mask can be used together with the Dräger powered air purifying respirators (e.g. X-plore® 7300 or 7500 series).

The mask body, which is made of robust and hypoallergenic EPDM, features a double-layer face seal with triple sealing action for a secure and comfortable fit on just about any shape of face. The mask comes in a universal "one size fits all", making logistics and storage easy. The comfortable five-point head harness not

only ensures that the mask can be donned easily and quickly, but is wide enough to prevent any pressure points on the wearer's head. The scratch-proof and distortion-free PMMA Plexiglas visor with 180° wide-angle guarantees a large field of vision with panoramic view. The robust frame is made of extra-light plastic, and the intelligent ventilation system ensures that the visor remains fog-free.

A barcode inside the mask makes checking inventories and carrying out mask maintenance easy. Valves can even be serviced without tools. A full range of accessories and spare parts are available. High quality materials and careful workmanship ensure mask longevity, making the masks highly cost effective.

### TECHNICAL DATA

Mask body	Highly resistant and hypoallergenic EPDM
Visor	Scratch-proof PMMA (Plexiglas) with 180° wide-angle
Connector	Sturdy plastic with inhalation and exhalation valve, standard thread connection Rd 40x1/7" as per EN 148-1
Weight	Approx. 500 g
Tested and approved	EN 136 Class 2 (CE mark), NIOSH, AS/NZS



Dräger X-plore® 6300 EPDM/PMMA



**KaRo BV**  
Tulpenmarkt 4  
1681 PK Zwaagdijk

**T** 0228 - 56 31 35  
**E** info@karobv.nl  
**www.karobv.nl**

