


Checkvalve

Terugslagklep
Rückschlagventil
Soupape de retenue
Valvola diritegno
Vulvelas antiretorno

VITON

**groene
afdichting**



Art.code	d1	d2	d3	Z	C	DN	PN	P	Kv	Quantity
6.61.016	16	43	10	46	75	10	16	0.05	61	50
6.61.020	20	59	17	58	91	15	16	0.05	147	50
6.61.025	25	64	22	62.5	101.5	20	16	0.05	263	50
6.61.032	32	73	27	75.5	120.5	25	16	0.05	388	50
6.61.040	40	86	33	90	143	32	16	0.05	682	30
6.61.050	50	102	40	108	171	40	16	0.05	1052	10
6.61.063	63	124	50	129	205.5	50	16	0.05	1658	10
6.61.075	75	151	67	164	252	65	10	0.10	1933	1
6.61.090	90	178.5	83	188	291	80	10	0.10	3166	1
6.61.110	110	215.5	99	225	348	100	10	0.10	4650	1

P	Openingsdruk	Kv	Flow [l/min] waarbij Δp is 1 bar, bepaald volgens DIN EN 60534-2-3
	Opening pressure		Flow [l/min] by which Δp is 1 bar, determined according to DIN EN 60534-2-3
	Öffnungsdruck		Fluss [l/min] wobei Δp 1 bar ist, festgesetzt zufolge DIN EN 60534-2-3
	Pression d'ouverture		Courant [l/min] par lequel Δp est 1 bar, déterminé par DIN EN 60534-2-3
	Pressione in apertura		Corrente [l/min] fra cui Δp é 1 bar, determinato secondo DIN EN 60534-2-3
	Presión de apertura		Caudal [l/min] con un Δp de 1 bar, determinado según DIN EN 60534-2-3